

NOVUS LiftTEC arm III

The high-grade NOVUS LiftTEC®-arm III of diecast aluminium is a design highlight among monitor arms with a straight front arm element for optimum screen positioning.

A gas pressure spring allows the monitor height to be infinitely adjusted with just two fingers. The arm can be pivoted 180° in the working area, has a reach up to 515 mm and a ball-joint for almost unlimited freedom of movement. Setting the user's ideal position is consequently child's play and a change of posture possible at any time.

The quick-release mechanism with 1-lever operation allows any monitor weighing 3-8 kg or 7-15 kg to be attached without undue effort. It is equipped with the standard, widely used flat-screen mount 75 x 75 and 100 x 100 for the mounting of all normal flat-screens.

The monitor cables are guided through cable clamps and the cable entry in the base.

The table attachment allows the arm to be secured with a clamp, cable port or drilling screw fitting.



Equipment



The LiftTEC® arm with gas spring technology can be infinitely adjusted to any height with incredible ease.



The adapter plate permits the straightforward attachment of all monitors with the standard 75 or 100 mount.



The product can be turned to either side and has the mentioned reach in mm.



When used conventional.



This machine bears the GS approval of product safety.



The quality statement „German Engineering“ ensures that a product was developed according to german quality standards by our engineering experts. All Novus products carrying the German Engineering by Novus signet are manufactured in our own plants around the world by our own workforce, managed and supervised by our own headquarters in Germany.

Version



silver /
anthracite

Art.No.

930+3089+000

Bar code

4009729045398



silver /
anthracite

930+3159+000

4009729045404

NOVUS LiftTEC arm III



The LiftTEC[®] arm with convenient gas spring technology can be infinitely adjusted to any height with incredible ease.



The easy-action rotating joints can be adjusted to any position.



Cables are routed through the base of the LiftTEC arm.



Monitor is easy to attach using QuickRelease with single-lever operation. Ball-joint for selecting the optimum viewing angle as well as for utilising the monitor pivoting function.

NOVUS LiftTEC arm III



Cable clips for perfect cable management along and inside the support arm.



Adjustable gas springs allow the LiftTEC[®] arm to be adjusted to the weight of the monitor.



The monitor is attached and released with effortless ease thanks to the new, simple Quick Release system with single-lever operation.