



GENERAL TOLERANCES ACCORDING TO ISO 2768-mK	
NOMINALE SIZES TOL:	
0,5 to 3 mm	±0,1
>3 to 6 mm	±0,1
>6 to 30 mm	±0,2
>30 to 120 mm	±0,3
>120 to 400 mm	±0,5
>400 to 1000 mm	±0,8
NOMINALE RADIUS TOL:	
0,5 to 3 mm	±0,2
>3 to 6 mm	±0,5
>6 mm	±1
NOMINALE ANGLE TOL:	
to 10°	±1°
>10 to 50°	±30'
>50 to 120°	±20'
>120°	±10'
STRAIGHTNESS AND EVENNESS TOL:	
to 10 mm	±0,05
>10 to 30 mm	±0,1
>30 to 100 mm	±0,2
>100 to 300 mm	±0,4
>300 to 1000 mm	±0,6
SQUARENESS TOL:	
to 100 mm	±0,4
>100 to 300 mm	±0,6
>300 to 1000 mm	±0,8
SYMMETRY TOL:	
to 300 mm	±0,4
>300 to 1000 mm	±0,8
CIRCULARITY TOL:	
general	±0,2

MASTER BOX:
QTY: 4 PCS

DIM: 49.5x34x24 CM

PRODUCT BOX:
QTY: 1 PCS

DIM: 49x16.5x11.5 CM

MONITOR WEIGHT 8 KG
COLOR: BLACK - WHITE - SILVER
INCLUDING THROUGH TOP CONNECTION

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		DEBUR AND BREAK SHARP EDGES	
GENERAL TOLERANCES ACCORDING TO: ISO-2768 mK					
DRAWN	NAME	SIGNATURE	DATE	TITLE:	
CHKD				PHARO SINGLE MONITOR ARM	
APPVD					
MFG					
Q.A					
			MATERIAL:	DWG NO.	A3
			WEIGHT: gm/mc 3,95/1,32 kg	SCALE:1:5	SHEET 1 OF 1